

BBC-13X Sound Curtains

Sound Seal's **BBC-13X** offers the benefits of both a noise barrier and a sound absorber for outdoor applications. The BBC-13X consists of a one-inch thick vinyl-coated-fiberglass-cloth faced quilted fiberglass that is bonded to a one-pound per sq. ft. reinforced loaded vinyl noise barrier. **"X"** style Sound Curtain panels are constructed with grommets across the top and **bottom, and exterior grade** Velcro seals along the vertical edges. The product is also available in roll form with edges bound or unbound.



- Class A (or 1) flammability rated per ASTM E 84
- For use on Indoor or Outdoor Applications
- Available facing colors: gray, tan, black, or off-white
- Available barrier colors: gray, tan, blue or olive drab

Applications:

Even in the harshest environments, with a minimum life span of 5 years* and wind load ratings of 120 mph, this product is typically used as a **temporary noise barrier on outdoor applications such as construction site noise mitigation projects**. Also available with a two-pound psf noise barrier or a two-inch thick quilted fiberglass sound absorber for better acoustical performance.

Product Data:

Description	Vinyl coated fiberglass cloth facing on 1" quilted fiberglass 1lb-psf reinforced loaded vinyl barrier
Flammability	Flame Spread: 23.0 Smoke density: 30.0
Nominal thickness	1.0 inch
Temperature range	-20° to +180° F
Standard roll size	54" wide x 25' long
Weight	1.2 lb psf

Acoustical Performance:

Sound Transmission Loss

Product	OCTAVE BAND FREQUENCIES (Hz)						STC
	125	250	500	1000	2000	4000	
BBC-13 X	11	16	24	30	35	35	27

ASTM E-90 & E 413

Sound Absorption Data

Product	OCTAVE BAND FREQUENCIES (Hz)						NRC
	125	250	500	1000	2000	4000	
BBC-13 X	.12	.47	.85	.84	.64	.62	.70

ASTM C 423

* when properly installed.